



<http://wiki.homerecz.com>

- 1
- 1
- 1
- 1
- ESI Pro WaMi Rack 192X** 5
 - 5
 - 5
 - 5
 - 5
 - 5
 - 6
- E-WDM** 6
 - 6
 - 6
 - 6
 - 7
 - 7
 - 7
 - 7
- 10
- 10
- 10
- 10

ESI Pro WaMi Rack 192X

ESI Pro WaMi Rack 192X 192kHz

24, 96kHz, 192kHz, 192, 4, 8, S/PDIF I/O, MIDI, A-D/D-A I/O, 192kHz, 24

- **192kHz** : A-D/D-A 24 /192kHz
- **I/O**: 4 / , 8 , S/PDIF I/O, MIDI
- **E-WDM** : MME, DirectSound, **ASIO 2.0**, GSIF
- **DirectWire**: MME, **ASIO**, GSIF
- : 가

- :
 - 2 **XLR** (+48V).
 - / .
 - 4 (20dB).
 - ().
- :
 - 4 (TRS).
 - 8 (TRS).
 - 1/2 **XLR** .
 - **MIDI** .
 - **D-sub** (**PCI**).
 - ().

- **E-WDM (Enhanced Windows Driver Model)**: Windows 98SE, ME, 2000, XP .

- : 가 .
- : 가 .
- **DirectWire**: MME, [ASIO](#), GSIF .

- : 16kHz ~ 192kHz ().
- : , , .
- : 3/4 .
- **S/PDIF** : Pro ([AES-EBU](#)) Consumer (IEC 958 Type II) .
- : / (/), , , .
- **MME** : MME .
- **ASIO** : 48 ~ 2048 ().

E-WDM

E-WDM MME, DirectSound, [ASIO 2.0](#), GSIF ,
. DirectWire

192X , ' ' .
, 96kHz . 192kHz

[ASIO](#) . DirectWire [VST/DirectX](#)
GigaStudio 가 .

- : 4 , / [XLR](#), 1.5kΩ, +48V ().
- : 4 , / [TRS](#), 10kΩ.
- : +4dBu , +22dBu , +20dB .
- : 8 , , / [TRS](#), 100Ω, +4dBu.
- : 123dBA (-60dBFS).
- **A-D** : 24 128x , .

- **D-A** : 24 128x , 8x .
- : 106dBA.
- : 6.5Hz ~ 87kHz (±0.05dB) @ 192kHz.
- : 16, 24, 32 float.
- : 16, 22, 24, 32, 44.1, 48, 88.2, 96, 176.4, 192kHz.
- **I/O**: , 32kHz ~ 192kHz.
- **MIDI**:


-
- E-WDM DirectWire .
-
- 192kHz


- S/PDIF (,) .
-


ESI Pro WaMi Rack 192X

- <https://www.soundonsound.com/reviews/esi-pro-wami-rack-192x>









<http://wiki.homerecz.com>

From:

<https://wiki.homerecz.com/> -

Last update: **2025/04/05**

: (admin@homerecz.com)