



<http://wiki.homerecz.com>

.....	1
.....	1
.....	1
.....	1
Generic low latency ASIO driver	5
.....	7
.....	7
.....	7
.....	7

Generic low latency ASIO driver

Windows OS Steinberg DAW ASIO
(Generic ASIO Driver : ASIO)

가 ASIO ASIO
ASIO ASIO . MAC OS Core Audio Driver가
가 , Windows WASAPI ASIO
, Steinberg Windows
가 ASIO .

, ASIO .

ASIO4ALL .

ASIO , 가 가
가 .

Generic Low Latency ASIO Driver - Version 1.0.21.10 - x64

Card Options

☒

Allow ASIO host application to take exclusive control of selected port configuration. This can affect the number of available input and output ports.

Sample rate

48000

Input/Output port configuration can differ for each sample rate.

Audio buffer size

☐ User definable

Selected buffer size:

100

 milliseconds

smallmiddlelarge

Output Ports

Device Name	Audio Channel	Bits per Sample
☒ 스피커(Realtek(R) Audio)	2	24

스피커(Realtek(R) Audio)

Input Ports

Device Name	Audio Channel	Bits per Sample
☐ 마이크(Realtek(R) Audio)	2	16
☐ 라인(NewTek NDI Audio)	2	16

-

Help

Cancel

OK



<http://wiki.homerecz.com>

From:
<https://wiki.homerecz.com/> -

Last update: **2024/03/22**

: (admin@homerecz.com)