



<http://wiki.homerecz.com>

.....	1
.....	1
.....	1
.....	1
BJT FET	5
BJT	5
FET	5
.....	5
SMD vs Through-hole	6
.....	6
Reference	6
.....	7
.....	7
.....	7
.....	7

BJT FET

BJT FET

Neve 1073 6

가

가

가

BJT

BJT Current Gain(HFE)

BJT ±20%

(VBE)

가

- **Current Gain(HFE):**

BJT Current Gain
Current Gain

±20%

• (VBE): VBE

가

BJT

± 2% ± 10%

FET

FET BJT

(VGS)

FET

- : FET
, MOSFET
± 1%

±10%

MOSFET

BJT FET

- **BJT:** 가 BJT (VBE) 2mV/°C , BJT
BJT
- **FET:** FET (VGS) (Vth) FET
가 가 가 가 , 가

SMD vs Through-hole

SMD Through-hole

- **SMD**

, 가
,

- **Through-hole**

가 가 . 가

BJT FET

가 . SMD 가 가 , Through-hole

Reference

- “**Transistor Matching and Effects on Audio Amplifier Performance,**” Journal of Audio Engineering Society.
- “**The Influence of Temperature on Semiconductor Devices,**” IEEE Transactions on Semiconductor Manufacturing.



<http://wiki.homerecz.com>

From:
<https://wiki.homerecz.com/> -

Last update: **2025/03/17**

: (admin@homerecz.com)